IN THE CLAIMS:

Please cancel claims 1-20, and add new claims 21-44 as follows:

- 1.-20. (Canceled)
- 21. (New) A method of providing computer resource access rights to a process, comprising:

providing a memory storing meta-data, the meta-data defining resource access rights of the process;

receiving a request from the process to authenticate a user;
authenticating the user responsive to the request from the process; and
responsive to a positive authentication of the user, altering the meta-data in the
memory to provide the process with resource access rights defined for the
process.

- 22. (New) The method of claim 21,
 wherein the meta-data stored in the memory initially has a null value; and
 wherein altering the meta-data in the memory comprises:
 substituting the null value with an identification of the user.
- 23. (New) The method of claim 21, wherein authenticating the user responsive to the request from the process comprises:

providing the user with a first value;

receiving a user identification and a second value from the process, the second value generated responsive to a password and the first value; generating the password from the first and second values; and authenticating the user responsive to the username and the password.

24. (New) The method of claim 21, wherein authenticating the user responsive to the request from the process comprises:

providing the user with a first value;

receiving a user identification and a second value from the process, the second value generated responsive to the first value and a password provided by the user; identifying a password associated with the received user identification; generating a third value from the first value and the password associated with the received user identification; and positively authenticating the user if the generated third value matches the received

positively authenticating the user if the generated third value matches the received second value.

- 25. (New) The method of claim 24, wherein generating the third value from the first value and the password associated with the received user identification comprises:

 applying a hash function to the first value and the password associated with the received user identification.
 - 26. (New) The method of claim 21, wherein the memory stores a directory path; and further comprising:

responsive to the positive authentication of the user, providing the process with resource access rights to one or more resources located in a directory within the directory path, the directory being designated by the altered meta-data.

- 27. (New) The method of claim 21, further comprising: storing data in the memory indicating that the process has made a request to authenticate the user.
- 28. (New) The method of claim 27, further comprising:
 responsive to receiving a user identification from the user, verifying that the data in
 the memory indicates that the process has made a request to authenticate the
 user.

29. (New) A system for providing computer resource access rights to a process, comprising:

a memory for storing meta-data, the meta-data defining resource access rights of the process;

an interface module for receiving a request from the process to authenticate a user; a validation module for authenticating the user responsive to the request from the process; and

- a security module for altering, responsive to a positive authentication of the user, the meta-data in the memory to provide the process with resource access rights defined for the process.
- 30. (New) The system of claim 29,
 wherein the meta-data stored in the memory initially has a null value; and
 wherein the security module is adapted to substitute the null value with an
 identification of the user responsive to the positive authentication of the user.
 - (New) The system of claim 29, wherein the validation module is adapted to:
 provide the user with a first value;
 receive a user identification and a second value from the process, the second value
 generated responsive to a password and the first value;
 generate the password from the first and second values; and
 authenticate the user responsive to the username and the password.
- 32. (New) The system of claim 29, wherein the validation module is adapted to:

 provide the user with a first value;

 receive a user identification and a second value from the process, the second value

 generated responsive to the first value and a password provided by the user;

 identify a password associated with the received user identification;

generate a third value from the first value and the password associated with the received user identification; and

positively authenticate the user if the generated third value matches the received second value.

33. (New) The system of claim 32, wherein the validation module is adapted to generate the third value by:

applying a hash function to the first value and the password associated with the received user identification.

34. (New) The system of claim 29, wherein the memory is adapted to store a directory path; and wherein the security module is adapted to:

provide, responsive to the positive authentication of the user, the process with resource access rights to one or more resources located in a directory within the directory path, the directory being designated by the altered meta-data.

- 35. (New) The system of claim 29, wherein the memory is adapted to: store data indicating that the process has made a request to authenticate the user.
- 36. (New) The system of claim 35, wherein the validation module is adapted to:

 verify, responsive to receiving a user identification from the user, that the data in the

 memory indicates that the process has made a request to authenticate the user.
- 37. (New) A computer program product having a computer-readable medium having embodied thereon program code for providing computer resource access rights to a process, the program code comprising:

a memory module for storing meta-data, the meta-data defining resource access rights of the process;

an interface module for receiving a request from the process to authenticate a user; a validation module for authenticating the user responsive to the request from the process; and

- a security module for altering, responsive to a positive authentication of the user, the meta-data in the memory module to provide the process with resource access rights defined for the process.
- 38. (New) The computer program product of claim 37, wherein the meta-data stored in the memory module initially has a null value; and wherein the security module is adapted to substitute the null value with an identification of the user responsive to the positive authentication of the user.
- 39. (New) The computer program product of claim 37, wherein the validation module is adapted to:

provide the user with a first value;

receive a user identification and a second value from the process, the second value generated responsive to a password and the first value; generate the password from the first and second values; and authenticate the user responsive to the username and the password.

40. (New) The computer program product of claim 37, wherein the validation module is adapted to:

provide the user with a first value;

receive a user identification and a second value from the process, the second value generated responsive to the first value and a password provided by the user; identify a password associated with the received user identification; generate a third value from the first value and the password associated with the received user identification; and positively authenticate the user if the generated third value matches the received second value.

41. (New) The computer program product of claim 40, wherein the validation module is adapted to generate the third value by:

applying a hash function to the first value and the password associated with the received user identification.

42. (New) The computer program product of claim 37, wherein the memory module is adapted to store a directory path; and wherein the security module is adapted to:

provide, responsive to the positive authentication of the user, the process with resource access rights to one or more resources located in a directory within the directory path, the directory being designated by the altered meta-data.

43. (New) The computer program product of claim 37, wherein the memory module is adapted to:

store data indicating that the process has made a request to authenticate the user.

44. (New) The computer program product of claim 43, wherein the validation module is adapted to:

verify, responsive to receiving a user identification from the user, that the data in the memory module indicates that the process has made a request to authenticate the user.